

Smart Charger Implementation Examples & Architectures

Dale Stoltzka, National
Semiconductor Corporation




Topics

- Typical Battery-controlled Charging
- Review Smart Charger Characteristics
- A litmus test for Battery-controlled SBC's
- Non-compliant architectures
- Host-controlled Charging (a.k.a., Level 3)
- Multiple-battery systems
- Thermistor pin Examples

Cautionary Note


- This presentation highlights some compliant and non-compliant charging architectures.
- Even if the architecture is compliant to the SBS specifications, this does not warrant or make any recommendations about the applicability of a specific charging method to a particular battery or cell chemistry.
- The SBS specifications are intended to give the implementor freedom to implement specific architectures of choice.

Typical Single Battery System



"Smart Charger Implementation Examples..." by National Semiconductor

SBC Characteristics




"Smart Charger Implementation Examples..." by National Semiconductor

Battery-controlled Charging Litmus Test

- Requires *ChargingCurrent* and *ChargingVoltage* be refreshed periodically, else stop?
- Stop if current or voltage request is 0?
- Stop if battery's Therm pin is out-of-range?
- Stop if any *AlarmWarning* bits[15:12] are True?
- Stop if wake-up charge time limit is exceeded?
- Does not load the bus nor battery when off or inactive?

Level 1 Charger is Non-compliant


- *Is not chemistry-independent*
 - *Charger is either On or Off*
 - *Voltage and current values are fixed*
 - *Not defined in version 1.0*



"Smart Charger Implementation Examples..." by National Semiconductor

Pulsing Battery-controlled Charger

- The SBC may not pulse the battery




Pulsing Battery-controlled Charger

- This architecture is non-compliant
 - Duty-cycled current pulses exceed the safe current limit set by `ChargingCurrent()`
 - Safe operation relies on specific and chemistry-dependent factors
 - Does not meet 5% *ChargingCurrent* and *ChargingVoltage* accuracy over finite intervals

Battery Internally Controls Charging


- **CHARGE_CONTROLLER_ENABLED = 1**



"Smart Charger Implementation Examples..." by National Semiconductor

Battery Internally Controls Charging

- This architecture is compliant
 - The battery maintains periodic Charging-Current and ChargingVoltage messages
 - Battery modulates current, internally



"Smart Charger Implementation Examples..." by National Semiconductor


Host-controlled Charging (Level 3)

- Host-controlled charging generically refers to any Host that controls the battery charging. Hosts may be:
 - Smart Battery Charger (Level 3)
 - System Host with a built-in charger
 - System Host that manages the bus traffic by communicating directly to a slave SBC
 - ...

Host-controlled Charging Rules


- The Host must periodically poll the battery for charging current and voltage
 - Time period is not specified but periodic
- Battery still broadcasts AlarmWarning()
- The battery may still modulate current
- All other Litmus test rules apply
 - Thermistor ranges, etc.

SBC Contains the Host-controller



"Smart Charger Implementation Examples..." by National Semiconductor

System Host Contains the SBC




"Smart Charger Implementation Examples..." by National Semiconductor

Multiple Battery Systems

- Systems can contain up to 4 batteries
 - Battery Selector system can use 4
- Options may include, and not limited to:
 - One battery idle, one battery charges
 - One battery discharges, one charges
- May not charge two batteries simultaneously

Multiple Battery Systems




"Smart Charger Implementation Examples..." by National Semiconductor

Host-controlled "Pulse" Charging


- Let's charge up to 4 batteries
- Algorithm is in the Host-controlled SBC
- Disable broadcasting by battery
- The Host can look like it is pulse-charging each battery, in fact, the charger is time-sharing its output
- If time of each charge is < 10 sec, the Host must poll `BatteryStatus()`

A Host-controlled Charge Timing



"Smart Charger Implementation Examples..." by National Semiconductor

Host-controlled Multiple-battery Layout





"Smart Charger Implementation Examples..." by National Semiconductor

Thermistor Pin Issues

- Two time-limited wake-up modes
 - 0 to 500 Ω is a mode which time-limits wake-up charging = THERM_UR
 - 30k Ω - 100k Ω permits wake-up charging for a specific time period = THERM_COLD
- 3k Ω to 30k Ω permits indefinite wake-up charging

Thermistor Pin Examples

- Smart Charger is compliant with either:



Summary Review

- Keep safety first in mind!!!
- Use the litmus test for a SBC to help avoid non-compliant architectures
- Make charger system partitioning decisions around the Host. Is battery-controlled or host-controlled charging desired?
- Use multiple-battery systems with care
- Design Thermistor pin as a failsafe device